



Manufacturer: BIT-USA
Model: ICS-ONE
Device Type: Irrigation Controller

CONTACT SUPPORT:

COMPANY NAME:	DES, Inc.
EMAIL ADDRESS:	modulesupport@des3s.com
PHONE:	479-621-8889
ADDRESS:	2349 W Hudson Dr, Rogers, AR 72756

GENERAL INFORMATION

SIMPLWINDOWS NAME:	ICS-ONE Controller v1.0
CATEGORY:	Irrigation
VERSION:	1.0
SUMMARY:	Provides control to BIT-USA ICS-ONE Controller.
GENERAL NOTES:	The ICS-ONE and ICS-ONE UI modules must exist on the same program slot.
CRESTRON HARDWARE REQUIRED:	3-Series
VENDOR FIRMWARE:	12.6.2
VENDOR SETUP:	http://bit-usa.com/documentation/ The ICS-ONE controller acquires an IP address via DHCP automatically and does not offer an option to set a static IP address. We recommend using a DHCP reservation for the controller.



Manufacturer: BIT-USA
 Model: ICS-ONE
 Device Type: Irrigation Controller

CONTROL:

Connect	D	Opens a TCP connection to the controller for as long as the input is high. High/1 (level sensitive) = Open connection; Low/0 = Close connection
----------------	---	--

FEEDBACK:

[Connect_Status]	A	Indicates the status of the connection. 0d: Disconnected 1d: Connecting 2d: Connected
ID_Fb	A	Generated ID. Must be connected to an ICS-ONE UI module.

PARAMETERS:

Host	S	IP address of the controller.
Poll Frequency	A	Adjusts how often the poll query will be sent to the controller.

TESTING:

OPS USED FOR TESTING:	3-Series: 1.011.0001
SIMPL WINDOWS USED FOR TESTING:	4.02.56
DEVICE DB USED FOR TESTING:	62.01.001.00
CRES DB USED FOR TESTING:	49.06.005.00
SYMBOL LIBRARY USED FOR TESTING:	855
SAMPLE PROGRAM:	ICS-ONE Sample v1.0 MC3.smw
REVISION HISTORY:	v1.0 – Initial version