

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



GENERAL INFORMATION

SIMPLWINDOWS NAME:	AVPro Edge MXNet MultiDestinationRouter v1.2
CATEGORY:	AVPro Edge MXNet
VERSION:	1.2
SUMMARY:	<p>This module works in conjunction with the AVPro MXNet CommandProcessor v1.2 module and the AVPro MXNet DestinationRouter v1.2 module to generate simultaneous route command to multiple decoders. The full suite of AVPro MXNet modules includes:</p> <ul style="list-style-type: none">• AVPro MXNet CommandProcessor v1.2• AVPro MXNet Encoder v1.2• AVPro MXNet Decoder v1.2• AVPro MXNet SerialPort v1.2• AVPro MXNet IRPort v1.2• AVPro MXNet CEC v1.2• AVPro MXNet DestinationRouter v1.2• AVPro MXNet MultiDestinationRouter v1.2• AVPro MXNet VW DecoderAssign v1.2• AVPro MXNet VW Layout v1.2• AVPro MXNet VW LayoutRecall v1.2
GENERAL NOTES:	<p>This module requires one instance of the AVPro MXNet CommandProcessor v1.2 module to register with, and at least one instance of the AVPro MXNet DestinationRouter v1.2 module. Practical applications would require two or more DestinationRouter modules.</p>
CRESTRON HARDWARE REQUIRED:	4-Series processor, 3-Series processor
SETUP OF CRESTRON HARDWARE:	N/A
VENDOR FIRMWARE:	MXNet Control Box v2.28 MXNet Encoder v3.39 MXNet Decoder v4.21
VENDOR SETUP:	N/A

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



PARAMETERS:

Command_Processor_ID	The unique identifier of the command processor module that this module registers with.
MultiRoute Group	Specifies the MultiRoute Group ID this module controls. All AVPro MXNet DestinationRouter modules with this MultiRoute Group ID will be used to create a single, multi-route command sent to the control box. The command performs simultaneous switching to all decoders contained within the group.

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



CONTROL:

Source_Route	A	Integer value specifies the encoder with the matching Matrix Source Index parameter. Setting this source route before pulsing Take_MultiRoute applies this source route to all decoders belonging to the group. If this source route is not set, the multi-route command will be generated with the last sent source routes of the destination router.
Take_MultiRoute	D	Pulse to send the source route command specified by the Source_Route serial input.

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet

**FEEDBACK:**

None

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet

**TESTING:**

OPS USED FOR TESTING:	VC4 v4.0000.00007 CP4 v2.8000.00017 CP3 v1.8001.5061.26823
SIMPL WINDOWS USED FOR TESTING:	4.2000.00
CRES DB USED FOR TESTING:	215.0000.003.00
DEVICE DATABASE:	200.23500.001.00
SYMBOL LIBRARY USED FOR TESTING:	1177
SAMPLE PROGRAM:	AVPro Edge MXNet v1.2 Demo.smw
REVISION HISTORY:	v1.0 – Initial Release v1.1 – Fixed SerialPort transmitted and received data. – Made updates to allow a Wallplate Encoder to initialize with this suite. v1.2 – Isolated serial communication queue to provide device control responsiveness. – Corrected unsolicited data parsing impacting hotplug detected and resolution.