

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



GENERAL INFORMATION

SIMPLWINDOWS NAME:	AVPro Edge MXNet VW DecoderAssign v2.1
CATEGORY:	AVPro Edge MXNet
VERSION:	2.1
SUMMARY:	<p>This module works in conjunction with the AVPro MXNet CommandProcessor v2.1 module to represent a single row/column of a video wall layout. The full suite of AVPro MXNet modules includes:</p> <ul style="list-style-type: none">• AVPro MXNet CommandProcessor v2.1• AVPro MXNet Encoder v2.1• AVPro MXNet Decoder v2.1• AVPro MXNet SerialPort v2.1• AVPro MXNet IRPort v2.1• AVPro MXNet CEC v2.1• AVPro MXNet DestinationRouter v2.1• AVPro MXNet MultiDestinationRouter v2.1• AVPro MXNet VW DecoderAssign v2.1• AVPro MXNet VW Layout v2.1• AVPro MXNet VW LayoutRecall v2.1• AVPro MXNet 10G VW LayoutRecall v2.1
GENERAL NOTES:	<p>This module requires one instance of the AVPro MXNet CommandProcessor v2.1 module to register with and one instance of the VW Layout v2.1 or 10G VW Layout v2.1 to register with.</p>
CRESTRON HARDWARE REQUIRED:	4-Series processor, 3-Series processor
SETUP OF CRESTRON HARDWARE:	N/A
VENDOR FIRMWARE:	MXNet 1G Control Box v2.34 MXNet 1G Encoder v3.39 MXNet 1G Decoder v4.21 MXNet 10G Control Box v3.28 MXNet 10G Encoder v1.25 MXNet 10G Decoder v1.25
VENDOR SETUP:	N/A

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



PARAMETERS:

Command_Processor_ID	The unique identifier of the command processor module that this module registers with.
Layout ID	The unique identifier of the video wall layout managed by this module.
Matrix Destination Index	The unique identifier of the decoder associated with video wall layout.
Column	The column of the video wall layout this decoder is in.
Row	The row of the video wall layout this decoder is in.
Rotate	The display angle of rotation. Possible values include: <ul style="list-style-type: none">• 0 (Default)• 180• N/A (Rotation is not applicable for 10G decoders)

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet

**CONTROL:**

None

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet

**FEEDBACK:****Is_Online_Fb**

- D High to indicate that the matching endpoint is online and available for control. If the device is offline, the associated layout control will work.

Partner: AVPro Edge
Models: MXNet
Device Type: AVPro Edge MXNet



TESTING:

OPS USED FOR TESTING:	VC4 v4.0000.00007 CP4 v2.8001.00086.01 CP3 v1.8001.0214.01
SIMPL WINDOWS USED FOR TESTING:	4.2500.04
CRES DB USED FOR TESTING:	219.0500.001.00
DEVICE DATABASE:	200.28000.002.00
SYMBOL LIBRARY USED FOR TESTING:	1191
SAMPLE PROGRAM:	AVPro Edge MXNet v2.1 Demo.smw
REVISION HISTORY:	<ul style="list-style-type: none">v1.0 – Initial Releasev1.1 – Fixed SerialPort transmitted and received data.<ul style="list-style-type: none">– Made updates to allow a Wallplate Encoder to initialize with this suite.v1.2 – Isolated serial communication queue to provide device control responsiveness.<ul style="list-style-type: none">– Corrected unsolicited data parsing impacting hotplug detected and resolution.v2.0 – Added “Offline” functionality.<ul style="list-style-type: none">– Polling will happen more frequently but will only poll for one component’s states at a time. This prevents serial control from getting backed up behind a global system poll.v2.1 – Added volume support for applicable 10G decoders.<ul style="list-style-type: none">– Added support for 10G videowall support with “10G VW Layout”