

SIMPLWINDOWS NAME: Tandberg Vision 2000 IR Remote Emulation Macro

CATEGORY: Codec

VERSION: 1.0

SUMMARY: Emulates all functions on a standard Tandberg IR remote

GENERAL NOTES: This macro allows access to all functions provided on a standard Tandberg Infrared remote control. There is an input for each button on the remote. The response to any input will be the same as if the button were pressed on the infrared remote.

CRESTRON HARDWARE: ST-COM, CNXCOM

SETUP OF CRESTRON HARDWARE: Baud Rate - 9600
Parity - None
Data Bits - 8
Stop Bits - 1

VENDOR FIRMWARE: Tested with Software version B3.1

VENDOR SETUP: Use Data Port 1 to communicate with the Crestron system. The Tandberg codec should have data port 1 set to "control mode"

CABLE NUMBER: CNSP-121

CONTROL:

ALL-INPUTS D All inputs directly correspond to buttons on the Tandberg infrared remote control

FEEDBACK:

TANDBERG-TX\$ S Serial data signal to be routed to a 2-way RS232 com port

OPS USED FOR TESTING: 3.18.01

COMPILER USED FOR TESTING: SimplWindows Version 1.20.04

SAMPLE PROGRAM: TANDTSTD

REVISION HISTORY: None