

Certified Module



GENERAL INFORMATION				
SIMPLWINDOWS NAME:	Home Connect v1.0 Washer			
CATEGORY:	Misc.			
VERSION:	1.0			
SUMMARY:	This module monitors and controls washer appliances compatible with the <u>Home Connect</u> cloud platform. Home Connect is featured on a wide range of connected home appliances from Bosch, Siemens, Neff, Gaggenau and Thermador.			
GENERAL NOTES:	This module interacts with one physical appliance. If multiple washer appliances are required, one module for each appliance must be added to the solution. This module requires one instance of the Home Connect v1.0 Comm IP module for managing all communication to and from the appliance.			
	Refer to the BSH Home Appliance v1.0 Comm IP Help file for important instructions regarding control processor and module configuration.			
CRESTRON HARDWARE REQUIRED:	Crestron 3-Series processor.			
SETUP OF CRESTRON HARDWARE:	N/A			
VENDOR FIRMWARE:	N/A			
VENDOR SETUP:	N/A			



Certified Module



PARAMETERS:

Device ID

Setting indicates the unique ID (HAID) of the appliance this module will interact with.



Certified Module



CONTROL:		
Power On	D	Pulse to set the power state to on.
Power_Standby	D	Pulse to set the power state to standby.
Start_Program	D	Pulse to begin execution of the selected program.
Resume_Program	D	Pulse to resume the selected program from paused state.
Pause_Program	D	Pulse to temporarily halt execution of the selected program.
Stop_Program	D	Pulse to abort execution of the selected program.
Program_[x]_Select	D	Pulse to select the desired program. The program must be available in order to be selected. Selecting a program will refresh the options in the module (where " x " is the specific program name).
Temperature_[x]_Select	D	Pulse to select the desired temperature option.
SpinSpeed_[x]_Select	D	Pulse to select the desired spin speed option.



Certified Module



FEEDBACK:		
Device_Name	S	Text value indicates the friendly name of the appliance device.
Is_Initialized	D	Signal latched high indicates that all state values of the device have been refreshed in the module and that the module is ready to control the device.
Is_Connected	D	Signal latched high indicates the physical device is connected to the Home Connect cloud platform. When low, the device cannot be controlled through the module.
Power_Is_Enabled	D	Signal latched high indicates that device power can be controlled through the module.
Power_ls_On	D	Signal latched high indicates the device power state is on.
Power_Is_Standby	D	Signal latched high indicates the device power state is standby.
Remote_Control_Activation	D	Signal latched high indicates that device activation can be triggered remotely.
Remote_Start_Allowed	D	Signal latched high indicates the device allows programs to be started through the module. When low, the module will not be able to start a selected program.
Locally_Controlled	D	Signal latched high indicates the device is being controlled by a person in front of the appliance.
Run_Program_Allowed	D	Signal latched high indicates the device is in a state where a program can be started. Several states prohibit running a program, such as the appliance door being open.
Pause_Program_Allowed	D	Signal latched high indicates the device supports pausing the currently running program. This signal should be used to hide or show a "pause program" option on the user interface.
Resume_Program_Allowed	D	Signal latched high indicates the device supports resuming the currently running program. This signal should be used to hide or show a "resume program" option on the user interface.
Program_Running_Progress	A	Integer value indicates the completion percentage of the running program. Percentage range is from 0 to 65535.
Program_Elapsed_Time	S	Text value indicates the amount of time the selected program has been running in hours, minutes, and seconds, formatted as HH:MM:SS.
Program_Remaining_Time	S	Text value indicates the amount of time the selected program still requires for completion in hours, minutes, and seconds, formatted as HH:MM:SS.
Run_Program_Error	S	Text value indicates an error state that prevents the module from running the selected program.
Program_Active_Label	S	Text value indicates the friendly name of the active program.







Operation_Is_Inactive	D	Signal latched high indicates the device appliance is in inactive state. This state indicates the appliance power is in standby.
Operation_Is_Ready	D	Signal latched high indicates the device appliance is in ready state. The state indicates no program has been activated.
Operation_ls_DelayedStart	D	Signal latched high indicates the device appliance is in delayed start mode. The state indicates a program has been activated but has not been started yet.
Operation_Is_Running	D	Signal latched high indicates the device appliance is in running state. This state indicates a program is in progress.
Operation_Is_Paused	D	Signal latched high indicates the device appliance is in paused state. This state indicates a program is halted.
Operation_Is_ActionRequired	D	Signal latched high indicates the device appliance is in action required state.
Operation_Is_Finished	D	Signal latched high indicates the device appliance is in finished state. This state indicates a running program has completed.
Operation_Is_Error	D	Signal latched high indicates the device appliance is in error state.
Operation_ls_Aborting	D	Signal latched high indicates the device appliance is in aborting state. This state indicates a program has been terminated before completing normally.
Door_ls_Open	D	Signal latched high indicates the device appliance door is open. A program cannot be run while the door is open.
Door_ls_Closed	D	Signal latched high indicates the device appliance door is closed. The door must be closed in order to run a program.
Door_ls_Locked	D	Signal latched high indicates the device appliance door is locked.
Program_[x]_Is_Available	D	Each signal latched high indicates the program is supported by the device and can be executed through the module (where "x" is the specific program name).
Program_[x]_Is_Selected	D	Any signal latched high indicates the program is the currently selected program on the appliance (where "x" is the specific program name)
Program_Selected_Label	S	Text value indicates the friendly name of the currently selected program.
Program_Selected_Index	A	Integer value indicates the index value of the currently selected program. This value can be used to drive custom text for the selected program.
Temperature_Is_Avaialble	D	Signal latched high indicates the temperature option group is available to display to the user as part of the selected program.
Temperature_[x]_ls_Available	D	Each signal latched high indicates a selectable choice the user can make for the temperature option group as part of the selected program.

www.crestron.com



Certified Module



SpinSpeed_Is_Available	D	Signal latched high indicates the spin speed option group is available to display to the user as part of the selected program.
SpinSpeed_[x]_ls_Available	D	Each signal latched high indicates a selectable choice the user can make for the spin speed option group as part of the selected program.
Temperature_[x]_Is_Selected	D	Any signal latched high indicates the currently selected choice for the temperature program option.
Temperature_Selected_Label	т	Text value indicates the friendly name of the currently selected temperature program option.
Temperaure_Selected_Index	A	Integer value indicates the index value of the currently selected temperature program option. This value can be used to drive custom text for the selected option.
SpinSpeed_[x]_Is_Selected	D	Any signal latched high indicates the currently selected choice for the spin speed program option.
SpinSpeed_Selected_Label	т	Text value indicates the friendly name of the currently selected spin speed program option.
SpinSpeed_Selected_Index	A	Integer value indicates the index value of the currently selected spin speed program option. This value can be used to drive custom text for the selected option.







TESTING:

OPS USED FOR TESTING:	CP3 1.603.4242.34642
SIMPL WINDOWS USED FOR TESTING:	4.14.20
CRES DB USED FOR TESTING:	201.00.004.00
DEVICE DATABASE:	200.05.001.00
SYMBOL LIBRARY USED FOR TESTING:	1114
SAMPLE PROGRAM:	Home Connect v1.0 Demo IP CP3.smw
REVISION HISTORY:	v1.0 – Initial Release