

# **Certified Module**

### Partner: Lutron Model: HomeWorks QSX Device Type: Lighting



GENERAL INFORMATION			
SIMPLWINDOWS NAME:	Lutron HomeWorks QSX Lumaris CCT Zone Control v1.3		
CATEGORY:	Lighting		
VERSION:	1.3		
SUMMARY:	This module provides monitor and control capability for a Zone component as part of a Lutron HomeWorks QSX solution.		
GENERAL NOTES:	This module interacts with a single Lumaris CCT Zone component, if multiple Lumaris CCT Zone components need to be managed, one module can be added for each component in the solution. This module requires one instance of the Lutron HomeWorks QSX Command Processor module to register with.		
CRESTRON HARDWARE REQUIRED:	Crestron 3-Series or 4-Series processor.		
SETUP OF CRESTRON HARDWARE:	N/A		
VENDOR FIRMWARE:	23.08.14f000		
VENDOR SETUP:	Lutron HomeWorks QSX Processor		

Crestron Certified Integrated Partner Modules can be found archived on our website in the Design Center. For more information please contact our Technical Sales Department at techsales@crestron.com. The information contained on this document is privileged and confidential and for use by Crestron Authorized Dealers, CAIP Members, A+ Partners and Certified Integrated Partners only. Specifications subject to change without notice.

www.crestron.com



# **Certified Module**

### Partner: Lutron Model: HomeWorks QSX Device Type: Lighting



PARAMETER:	
Command_Processor_ID	Setting indicates the identifier of the Command Processor module this module registers with. A single program can contain multiple zone modules where multiple Lutron processors are involved.
Fade_Time	Setting indicates the time interval in seconds for lighting to adjust to a new level. Range is 0 to 14400.
Zone_Href_ID	Setting indicates the reference identifier for the zone this zone control belongs to. Example: for zone href: /Zone/1399, enter the value 1399 in the parameter field.

Crestron Certified Integrated Partner Modules can be found archived on our website in the Design Center. For more information please contact our Technical Sales Department at techsales@crestron.com. The information contained on this document is privileged and confidential and for use by Crestron Authorized Dealers, CAIP Members, A+ Partners and Certified Integrated Partners only. Specifications subject to change without notice.



#### Partner: Lutron Model: HomeWorks QSX Device Type: Lighting





CONTROL:		
Dim_Level	A	Integer value specifies the intensity level to set as a percentage. Range is 0d to 65535d.
Set_DimLevel	D	<ul><li>Pulse to set the discrete value of the intensity specified by the Dim_Level analog input signal.</li><li>For slider operations, use a press join to drive this signal high. When this is high, the corresponding analog value will be sent automatically on change. Using a '1' on a 'set' signal is discouraged and will have negative effect.</li></ul>
WhiteTuning_Level	A	Integer value specifies the white tuning (CCT) level in Kelvin. Maximum range is 1400d to 10000d. Allowed range is based on the range reported by the zone.
Set_WhiteTuningLevel	D	Pulse to set the discrete value of the integer specified by the WhiteTuning_Level analog input signal. For slider operations, use a press join to drive this signal high. When this is high, the corresponding analog value will be sent automatically on change. Using a '1' on a 'set' signal is discouraged and will have negative effect.
FadeTime	А	Integer value specifies the fade time in seconds. Range is 0d to 14400d.
WarmDim_ModifiedHalogen	D	Pulse to enable warm dimming on the Modified Halogen Curve (Id 1) with a CCT range of 10000K to 1400K. Disabled if the curve is not supported by the zone.
WarmDim_Finire2700K	D	Pulse to enable warm dimming on the Finire 2700K Curve (Id 2) with a CCT range of 2700K to 1800K. Disabled if the curve is not supported by the zone.
WarmDim_Finire3000K	D	Pulse to enable warm dimming on the Finire 3000K Curve (Id 3) with a CCT range of 3000K to 1800K. Disabled if the curve is not supported by the zone.
WarmDim_GenericDaylight	D	Pulse to enable warm dimming on the Generic Daylight Curve (Id 4) with a CCT range of 5000K to 2500K. Disabled if the curve is not supported by the zone.
WarmDim_Off	D	Pulse to disable warm dimming.

www.crestron.com

Crestron Certified Integrated Partner Modules can be found archived on our website in the Design Center. For more information please contact our Technical Sales Department at techsales@crestron.com. The information contained on this document is privileged and confidential and for use by Crestron Authorized Dealers, CAIP Members, A+ Partners and Certified Integrated Partners only. Specifications subject to change without notice.



#### Partner: Lutron Model: HomeWorks QSX Device Type: Lighting



**Certified Module** 

FEEDBACK:		
ls_Initialized	D	High indicates the module is initialized. The module is initialized when all component state information has been updated in the module to reflect current component state.
DimLevel_Fb	A	Integer value indicates the current intensity level as a percentage from 0d to 65535d.
WhiteTuningLevel_Fb	A	Integer value indicates the current white tuning level in Kelvin. Maximum range is 1400d to 10000d.
WhiteTuning_Range_Min_Fb	А	Integer value indicates the minimum white tuning level as reported by the zone.
WhiteTuning_Range_Max_Fb	A	Integer value indicates the maximum white tuning level as reported by the zone.
FadeTime_Fb	A	Integer value indicates the current fade time in seconds. Range is 0d to 14400d.
WarmDim_ModifiedHalogen_Fb	D	High indicates that warming diming is enabled using the Modified Halogen Curve (Id 1) with a CCT range of 10000K to 1400K.
WarmDim_Finire2700K_Fb	D	High indicates that warm dimming is enabled using the Finire 2700K Curve (Id 2) with a CCT range of 2700K to 1800K.
WarmDim_Finire3000K_Fb	D	High indicates that warm dimming is enabled using the Finire 3000K Curve (Id 3) with a CCT range of 3000K to 1800K.
WarmDim_GenericDaylight_Fb	D	High indicates that warm dimming is enabled using the Generic Daylight Curve (Id 4) with a CCT range of 5000K to 2500K.
WarmDim_Off_Fb	D	High indicates that warm dimming is disabled.
WarmDim_ModifiedHalogen_Supported	D	High indicates that the Modified Halogen Curve (Id 1) with a CCT range of 10000K to 1400K is supported by the zone based on the reported white tuning range.
WarmDim_Finire2700K_Supported	D	High indicates that the Finire 2700K Curve (Id 2) with a CCT range of 2700K to 1800K is supported by the zone based on the reported white tuning range.
WarmDim_Finire3000K_Supported	D	High indicates that the Finire 3000K Curve (Id 3) with a CCT range of 3000K to 1800K is supported by the zone based on the reported white tuning range.
WarmDim_GenericDaylight_Supported	D	High indicates that the Generic Daylight Curve (Id 4) with a CCT range of 5000K to 2500K is supported by the zone based on the reported white tuning range.

www.crestron.com

Crestron Certified Integrated Partner Modules can be found archived on our website in the Design Center. For more information please contact our Technical Sales Department at techsales@crestron.com. The information contained on this document is privileged and confidential and for use by Crestron Authorized Dealers, CAIP Members, A+ Partners and Certified Integrated Partners only. Specifications subject to change without notice.



## **Certified Module**

Partner: Lutron Model: HomeWorks QSX Device Type: Lighting



#### **TESTING:** CP3 1.801.5061.26823 **OPS USED FOR TESTING:** CP4 2.8000.00086 SIMPL WINDOWS USED FOR TESTING: 4.27 **CRES DB USED FOR TESTING:** 222.05 DEVICE DATABASE: 200.320 SYMBOL LIBRARY USED FOR TESTING: 1198 SAMPLE PROGRAM: Lutron HomeWorks QSX v1.3 Demo IP.smw **REVISION HISTORY:** v1.3 - Initial Release

**WWW.Crestron.com** Crestron Certified Integrated Partner Modules can be found archived on our website in the Design Center. For more information please contact our Technical Sales Department at techsales@crestron.com. The information contained on this document is privileged and confidential and for use by Crestron Authorized Dealers, CAIP Members, A+ Partners and Certified Integrated Partners only. *Specifications subject to change without notice*.