





GENERAL INFORMATION			
SIMPLWINDOWS NAME:	Lutron MyRoom XC Area Control v1.0		
CATEGORY:	Lighting, HVAC, Shades		
VERSION:	1.0		
SUMMARY:	This module provides monitor and control capability for an Area control component as part of a Lutron MyRoom XC solution.		
GENERAL NOTES:	This module interacts with a single Area component, if multiple Area components need to be managed, one module can be added for each component in the solution. This module requires one instance of the Lutron MyRoom XC Command Processor module to register with.		
CRESTRON HARDWARE REQUIRED:	Crestron 4-Series processor		
SETUP OF CRESTRON HARDWARE:	N/A		
VENDOR FIRMWARE:	24.02.17f000		
VENDOR SETUP:	Lutron MyRoom XC Processor		







PARAMETER:	
Command_Processor_ID	Setting indicates the identifier of the Command Processor module this module registers with. A single program can contain multiple zone modules where multiple Lutron processors are involved.
Fade_Time	Setting indicates the time interval in seconds for lighting to adjust to a new level. Range is 0 to 14400.
Area_Href_ID	Setting indicates the reference identifier for the Area this area control belongs to. Example: for area href: /Area/1399, enter the value 1399 in the parameter field.







CONTROL:		
Set_DimLevel	Pulse to set the discrete value of the brightness specified by the Dim_Level an input signal.	nalog
	D For slider operations, use a press join to drive this signal high. When this is hig corresponding analog value will be sent automatically on change. Using a '1' o 'set' signal is discouraged and will have negative effect.	
Dim_Level	A Integer value specifies the dim level to set as a percentage. Range is 0 to 655	535.
FadeTime	A Integer value specifies the fade time in seconds. Range is 0 to 14400.	







FEEDBACK:		
Is_Initialized	D	High indicates the module is initialized. The module is initialized when all component state information has been updated in the module to reflect current component state.
DimLevel_Fb	Α	Integer value indicates the current dim level as a percentage from 0 to 65535.
FadeTime_Fb	Α	Integer value indicates the current fade time in seconds. Range is 0 to 14400.







TESTING:

OPS USED FOR TESTING: CP4 2.8003.00056

SIMPL WINDOWS USED FOR TESTING: 4.30

CRES DB USED FOR TESTING: 225.05

DEVICE DATABASE: 200.350

SYMBOL LIBRARY USED FOR TESTING: 1205

SAMPLE PROGRAM: Lutron MyRoom XC v1.0 Demo IP.smw

REVISION HISTORY: v1.0 – Initial Release