





GENERAL INFORMATION			
SIMPLWINDOWS NAME:	Lutron MyRoom XC CCO Zone Control v1.0		
CATEGORY:	Lighting, HVAC, Shades		
VERSION:	1.0		
SUMMARY:	This module provides monitor and control capability for a CCO Zone component as part of a Lutron MyRoom XC solution.		
GENERAL NOTES:	This module interacts with a single CCO Zone component, if multiple CCO Zone components need to be managed, one module can be added for each component in the solution. This module requires one instance of the Lutron MyRoom XC Command Processor module to register with.		
CRESTRON HARDWARE REQUIRED:	Crestron 4-Series processor		
SETUP OF CRESTRON HARDWARE:	N/A		
VENDOR FIRMWARE:	24.02.17f000		
VENDOR SETUP:	Lutron MyRoom XC Processor		







PARAMETER:	
Command_Processor_ID	Setting indicates the identifier of the Command Processor module this module registers with. A single program can contain multiple zone modules where multiple Lutron processors are involved.
Zone_Href_ID	Setting indicates the reference identifier for the zone this zone control belongs to. Example: for zone href: /Zone/1399, enter the value 1399 in the parameter field.



Certified Module



CONTROL:		
CCOLevel_Open	D	Pulse to open a CCO level.
CCOLevel_Close	D	Pulse to close a CCO level.







FEEDBACK:		
Is_Initialized	D	High indicates the module is initialized. The module is initialized when all component state information has been updated in the module to reflect current component state.
CCOLevel_ls_Open	D	High indicates the CCO level is open.
CCOLevel_ls_Closed	D	High indicates the CCO level is closed.







TESTING:

OPS USED FOR TESTING: CP4 2.8003.00056

SIMPL WINDOWS USED FOR TESTING: 4.30

CRES DB USED FOR TESTING: 225.05

DEVICE DATABASE: 200.350

SYMBOL LIBRARY USED FOR TESTING: 1205

SAMPLE PROGRAM: Lutron MyRoom XC v1.0 Demo IP.smw

REVISION HISTORY: v1.0 – Initial Release