

Partner: Polycom
Model: VSX7000 & VSX8000
Device Type: Video Conference




GENERAL INFORMATION

SIMPLWINDOWS NAME:	Polycom VSX7000 & VSX8000 Basic Control
CATEGORY:	Conferencing
VERSION:	1.0
SUMMARY:	Provides control of Volume, Privacy and PIP.
GENERAL NOTES:	<p>This module is for control of the Polycom VSX7000 & VSX8000.</p> <p>You can communicate with these systems over RS232 or over TCP/IP. If using TCP/IP, follow these instructions:</p> <p>You MUST open up a Telnet session with the Polycom system. Therefore, you must have an Ethernet enabled control system.</p> <p>When programming the system in SimplWindows, you should insert a TCP/IP Client object into the Ethernet portion of the control system, in the configuration manager. In the program view, use 24D for the PORT parameter field. When it is desired to establish the Telnet session with the Polycom system, assert the CONNECT input on the TCP/IP Client. When the session has been successfully established, the CONNECT-F output will go high. It will then be possible to send commands to the Polycom system. When it is desired to end the Telnet session, de-assert the CONNECT input, and the connection will be dropped.</p> <p>Commands should only be sent to the TCP/IP Client TX\$ input when the connection is active. Therefore, you should connect the output of this module to the input of a Serial Buffer symbol, which is enabled by the CONNECT-F output of the TCP/IP Client. The output of the Serial Buffer should be connected to the TX\$ input of the TCP/IP Client. See the demo program for an example of this implementation.</p> <p>Note that before resetting the Crestron system (as happens when you load a new program, power cycle the system, etc), you should end the Telnet session with the Polycom system. If the session is active when the Crestron system resets, the session will not be closed properly, and the Polycom system may need to be rebooted to recover properly.</p> <p>This module provides control of volume, privacy, PIP, sleep/wake and Visual Concert Play/Stop. True feedback for volume level, Privacy state, PIP state, sleep/wake state and Visual Concert Play/Stop states are provided. For this feedback to work properly, you must first use the Polycom VSX7000 & VSX8000 Initialization module to enable the real time reporting.</p> <p>NOTE: PIP WILL ONLY BE DISPLAYED WHILE A CALL IS IN PROGRESS.</p>
CRESTRON HARDWARE REQUIRED:	CNXENET+, C2ENET-1, C2ENET-2, CNXCOM, C2COM, ST-COM

Partner: Polycom
Model: VSX7000 & VSX8000
Device Type: Video Conference



SETUP OF CRESTRON HARDWARE:	<p>TCP/IP: Install a TCP/IP Client Use port 24D. Be sure the set up the IP table to specify the IP address of the Polycom system for the IP ID of the TCP/IP Client. You MUST do a cold reboot of the control system after changing these parameters.</p> <p>RS232: Baud: 9600 Parity: None Data Bits: 8 Stop Bits: 1</p>
VENDOR FIRMWARE:	Snowbird 7.0
VENDOR SETUP:	You must set one of the com ports on the VSX to control mode.
CABLE DIAGRAM:	CNSP-124



Partner: Polycom
Model: VSX7000 & VSX8000
Device Type: Video Conference


CONTROL:

Volume_Up/Down	D	Press and hold to adjust the volume.
Volume_Mute_<state>	D	Pulse to turn the volume mute on and off.
Privacy_<state>	D	Pulse to activate and deactivate privacy.
PIP_<state>	D	Pulse to select PIP On/Off/Auto.
Sleep/Wake	D	Pulse to enter and exit sleep mode on the Polycom.
From_Device\$	S	Serial signal to be routed from a 2-way serial com port or from the TCP/IP Client.

FEEDBACK:

Volume_Level	A	True feedback indicating the current volume level.
Volume_Mute_<state>_Fb	D	High to indicate that the volume level is at 0.
Privacy_<state>_Fb	D	True feedback indicating the current state of privacy.
PIP_<state>_Fb	D	True feedback indicating the last PIP mode activated.
Sleep/Wake_Fb	D	True feedback indicating the current sleep mode state.
To_Device\$	S	Serial signal to be routed to a 2-way RS232 com port or to the TCP/IP Client.

TESTING:

OPS USED FOR TESTING:	PRO2: 3.137 CNMSX: 5.14.02x
COMPILER USED FOR TESTING:	2.05.22
SAMPLE PROGRAM:	Polycom VSX7000 & VSX8000 Demo
REVISION HISTORY:	V. 1.0 – Original release.