

Partner: Xilica
Model: Solaro Series
Device Type: Digital Signal Processor



GENERAL INFORMATION

SIMPLWINDOWS NAME:	Xilica Solaro v1.0 Router Control
CATEGORY:	DSP
VERSION:	1.0
SUMMARY:	This module controls router blocks in the device.
GENERAL NOTES:	This module is used to control router type control points. It accepts an index value for selection and provides feedback for the currently routed index value.
CRESTRON HARDWARE REQUIRED:	3 Series processor only
VENDOR FIRMWARE:	v4.0.1

Partner: Xilica
Model: Solaro Series
Device Type: Digital Signal Processor

**CONTROL:**

Selection	A	Defines the value to be routed when Select is triggered.
Select	D	Pulse to send the value defined by the Selection signal.

Partner: Xilica
Model: Solaro Series
Device Type: Digital Signal Processor

**FEEDBACK:**

Initialized	D	Set to high when the module has successfully received the required responses to all queries.
Current_Selection	A	Indicates the currently routed index.

Partner: Xilica
Model: Solaro Series
Device Type: Digital Signal Processor

**PARAMETERS:**

Command Processor ID	A	Setting to indicate the ID for the command processor that this module will register itself with.
Control Object ID	S	Explicitly defines the control point the module should use. Control ID's are defined on the device and must match exactly.

Partner: Xilica
Model: Solaro Series
Device Type: Digital Signal Processor

**TESTING:**

OPS USED FOR TESTING:	CP3 1.601.3935.27221
SIMPL WINDOWS USED FOR TESTING:	4.11.06.01
CRES DB USED FOR TESTING:	86.00.002.00
DEVICE DATABASE:	113.05.001.00
SYMBOL LIBRARY USED FOR TESTING:	1101
SAMPLE PROGRAM:	Xilica Solaro v1.0 Demo
REVISION HISTORY:	v1.0 – Initial Release